

AMENDMENTS TO THE CLAIMS

This listing of claims will replace all prior versions and listings of claims in the application:

LISTING OF CLAIMS

1. (currently amended) A controller chip comprising:

a graphics engine operative to manage a memory, the graphics engine comprising an integral interface; and

a ~~storage element~~ first in first out (FIFO) buffer coupled to the graphics engine, the ~~storage element~~ FIFO buffer being accessible by a central processing unit (CPU) through the graphics engine, wherein the graphics engine receives commands from the CPU via the integral interface, and manages the ~~storage element~~ FIFO buffer via the integral interface ~~and writes the commands into the memory and wherein the graphics engine incorporates the storage element as part of the memory.~~

2. (canceled)

3. (currently amended) The controller chip of claim 21 in which the FIFO buffer comprises a circular FIFO buffer.

4. (currently amended) The controller chip of claim 21 in which the FIFO buffer comprises a double buffer.

5. (currently amended) The controller chip of claim 21 in which the FIFO buffer comprises a triple buffer.

6. (original) The controller chip of claim 3 wherein the effective size of the FIFO buffer

as viewed by the CPU can be as large as the memory.

7. (currently amended) The controller chip of claim 21 which includes a checking mechanism for determining if the FIFO buffer needs to be emptied without utilizing the CPU.

8. (original) The controller chip of claim 7 wherein the checking mechanism comprises:

means for calculating the time required to fill the FIFO buffer;

means for determining if the used memory of the FIFO buffer, is below a predetermined amount based upon the time required to fill the FIFO buffer; and
means for preventing the FIFO buffer from filling if the used memory in the FIFO buffer is over the predetermined amount.

9. (original) The controller chip of claim 1 wherein the controller chip comprises a graphics controller chip.

10. (original) The controller chip of claim 9 wherein the engine comprises a graphics engine.

11. (currently amended) A system for providing a command stream in a computer system comprising:

a central processing unit (CPU);

a controller coupled to the CPU and including a graphics engine comprising an integral interface;

a memory coupled to the controller, the memory being managed by the controller; and

a ~~storage element~~ first in first out (FIFO) buffer coupled to the controller, the storage element being accessible by the CPU through the controller, wherein the controller receives

commands from the CPU via the integral interface manages the storage element via the integral interface and writes the commands into the memory, ~~and wherein the controller incorporates the storage element as part of the memory.~~

12. (canceled)

13. (currently amended) The system of claim ~~12~~11 in which the FIFO buffer comprises a circular FIFO buffer.

14. (currently amended) The system of claim ~~12~~11 in which the FIFO buffer comprises a double buffer.

15. (currently amended) The system of claim ~~12~~11 in which the FIFO buffer comprises a triple buffer.

16. (currently amended) The system of claim ~~12~~11 in which the controller comprises a graphics controller.

17. (currently amended) The system of claim ~~12~~11 wherein the effective size of the FIFO buffer can be as large as the memory.

18. (currently amended) The system of claim ~~12~~11 which includes a checking mechanism for determining if the FIFO buffer needs to be emptied without utilizing the CPU.

19. (original) The system of claim 18 wherein the checking mechanism comprises:

means for calculating the time required to fill the FIFO buffer;

means for determining if the FIFO buffer is below a predetermined amount

based upon the time required to fill the buffer; and

means for preventing the FIFO buffer from filling if the FIFO buffer is above the predetermined amount.

20. (currently amended) A method for providing a command stream in a computer system, the computer system including a central processing unit (CPU), a controller coupled to the CPU, a memory coupled to the controller, the memory being managed by the controller, the method comprising the steps of:

(a) providing a ~~storage element~~ first in first out (FIFO) buffer within the controller; and

(b) allowing the ~~storage element~~ FIFO buffer to be accessible by the CPU via an integral interface ~~in~~ of a graphics engine of the graphics controller, ~~and wherein the controller incorporates the storage element as part of the memory.~~

21. (canceled)

22. (currently amended) The method of claim ~~21~~20 in which the FIFO buffer comprises a circular FIFO buffer.

23. (currently amended) The method of claim ~~21~~20 in which the FIFO buffer comprises a double buffer.

24. (currently amended) The method of claim ~~21~~20 in which the FIFO buffer comprises a triple buffer.

25. (currently amended) The method of claim ~~21~~20 in which the memory comprises a graphics memory.

26. (currently amended) The method of claim ~~24~~20 wherein the effective size of the FIFO buffer as viewed by the CPU can be as large as the memory.

27. (currently amended) The method of claim ~~24~~20 which includes the step of (c) determining if the FIFO buffer needs to be emptied without utilizing the CPU.

28. (original) The method of claim 27 wherein the determining step (c) further comprises:

(c1) calculating the time required to fill the FIFO buffer;

(c2) determining if the FIFO buffer is below a predetermined amount based upon the time required to fill the buffer; and

(c3) preventing the FIFO buffer from filling if the FIFO buffer is above the predetermined amount.